

NDA 701

Dumas Nitrogen Analyzer

Nitrogen / Protein
Determination in a Flash!



NDA 701 is the innovative VELP Scientifica solution for nitrogen/protein determination, using the Dumas method (also known as combustion method) and offering on both solid and liquid samples. NDA 701 works in accordance with a variety of Standards (such as AOAC, AACC, ASBC, ISO, IFFO, OIV, etc.).

NDA 701 Dumas Nitrogen Analyzer

The new and completely innovative step forward for nitrogen determination by VELP Scientifica. VELP is now able to offer different solutions for nitrogen determination, from the standard Kjeldahl method to the flash of Dumas combustion. In accordance with the Dumas method, NDA 701 is ideal for high throughput, being fully automated and requiring just 3-4 minutes per analysis.

Must be connected to



Can be connected to




NDA 701 Dumas Nitrogen Analyzer



Analysis in a Flash!
Fully automated, high productivity, 24/7 operation.



Eco-Friendly
Limited energy consumption, stand-by and Helium-saving mode and no wastes.




Long-life VELP Consumables

Minimum Maintenance
Monitoring of consumables, no daily calibration, no use of corrosive chemicals.

Precision and Accuracy
High repeatability, very low detection limit (0.003 mg N).

Analysis Flowpath



Combustion Reactor (CF)
Physical Water Trap (WT1)
Reduction Reactor (RF)
Chemical Water Trap (WT2)
CO₂ Regenerating Adsorbers (CO₂)
Innovative TCD (TCD)

allows combustion at 1030 °C in order to break all of the sample into its elemental substances. The maintenance-free DriStep™ cooler permits 99% of water to be removed.
enables the elimination of unwanted compounds and oxygen, transforming NO_x into N₂.
eliminates the residual water.
used to get rid of all the CO₂. Auto-regenerating, maintenance-free system.
LoGas™ determines nitrogen content without the need for a reference gas. Maintenance-free.

Features and Benefits

- Fast
- Fully Automated for Unsupervised Analysis
- Long Lifespan
- Flexible and Versatile
- Compact Profile
- Safe

GLP Good Laboratory Practice
AOAC • AACC • ASBC
ISO • IFFO • OIV

The autosampler can hold up to 116 samples (both solids and liquids) loaded in tin capsules. The samples need to be accurately homogenized, in order to maximize the results precision and to achieve a representative analysis.



TEMS technology saves
Time, Energy, Money and Space

- Time Saving: Unparalleled productivity, results in only 3-4 minutes
- Energy Saving: Excellent engineering, low consumption
- Money Saving: Limited cost per analysis, less gas and reagent used (LoGas™ and DriStep™)
- Space Saving: Just one slim unit required for the whole analysis



DUMASoft™ SOFTWARE

NDA 701 is completely controlled and operated by the DUMASoft™ software, offering all the most important info at a glance in one window!



...before the analysis

Simply position the capsule in the autosampler, enter sample name, type and weight and select the method and the calibration curve. Automatically, the software will set the analytical conditions according to the entered data. The dosing of gases is optimized by the software, in order to achieve complete combustion of the sample with minimum consumption. Create and save calibration curves using standards, pure test substances with a well-known nitrogen content. No need to create a new calibration curve every day. Recall it before starting the analysis. A good calibration curve requires 5-6 points. These should represent different standard quantities (in mg) to create a range (in mg of nitrogen) that will then contain the nitrogen content of the analyzed sample. The more that the content of mg of nitrogen is centered in the range, the greater are the accuracy and precision of the analysis. The software accepts weight values directly from the balance.



...during the analysis

In the main window the user can continuously check the instrument status, controlling the flow rate and the reactor temperatures on the right side of the page. Beneath, the user can also read suggestions about the maintenance, monitoring the number of analyses that can be performed before the next replacement. The real time graph shows the progress of the analysis, creating the peak as soon as the nitrogen starts reaching the Thermal Conductivity Detector (TCD).



...after the analysis

Once the analysis is completed, the operator will find all the test information in the main window, with a real-time graph, info about the method and results in different formats (nitrogen mg, nitrogen % and protein %). All analysis data are stored into databases and can be exported in .xls, .txt and .csv format to PC or LIMS. The operator can also create test reports for a single test or multiple analyses for a better interpretation of the data. Results can be also recalculated using different calibration curves, without performing a new test, but only selecting the new curve. A particularly useful additional function can be the reintegration of the peak area. Results can be output to a printer.

DUMAS

- **High Productivity** - Non-stop performance
- **Time Saving** - Few minutes required
- **Low Cost of Ownership** - Moderate running costs
- **Totally Unsupervised** - Fully automated process
- **Dry Chemistry** - No chemicals
- **Eco-friendly** - Less residues and no wastes produced
- **Officially recognized method** - Gaining in international use with advanced instruments

KJELDAHL

- **Less Productivity** - Inability to operate continuously
- **Time-consuming** - Analyses last hours
- **Affordable Equipment Cost**
- **Partly Unsupervised** - Not entirely automated process
- **Wet Chemistry** - Uses chemicals
- **Costly Wastes Produced** - Residues must be disposed of
- **Worldwide Official Method** - Traditional technique, simple equipment

Fields of Application

The NDA 701 is extremely versatile, being suitable for nitrogen and protein determination in several kinds of sample, in accordance with official AOAC, AACC, ASBC, ISO and OIV methods.



Food, feed and beverage industry



Environmental industry



Pharmaceutical and chemical industry

Fields of Application

| INSTRUMENT | POWER SUPPLY | CODE No |
|---------------------------------|------------------|-----------|
| NDA 701 Dumas Nitrogen Analyzer | 230 V / 50-60 Hz | F30800070 |

| OPTIONAL ACCESSORIES | CODE No |
|-------------------------------|-----------|
| Chromosorb, 10 g | A00000148 |
| Quartz wool, 50 g | A00000154 |
| Reduced copper, 250 g | A00000155 |
| Copper oxide, 50 g | A00000157 |
| VHT catalyst, 50 g | A00000159 |
| VLT catalyst, 25 g | A00000160 |
| Sicapent, 100 g | A00000171 |
| EDTA, 100 g | A00000149 |
| Tin Foil Cups, 100 pcs | A00000153 |
| Quartz reactor tube | A00000162 |
| Ash collector | A00000161 |
| 1000 analyses kit for NDA 701 | A00000194 |
| Disc 2 for autosampler | A00000199 |
| Disc 3 for autosampler | A00000200 |
| Disc 4 for autosampler | A00000201 |
| Tin foil cup closing device | A00000217 |

SUPPLIED WITH



- A00000193** Start-up kit
- 40001065** Autosampler with disc 1
- 40001504** NDA 701 DUMASoft™ Software
- 40001693** USB cable for PC, 5m
- 10003926** RS232 Cable for balance

The Dumas Analyzer contains all necessary parts to perform up to 1000* analyses (inclusive of catalysts, copper, quartz wool, reagents and seals). In addition it contains chemicals and small consumables spares for maintenance. Consumables and spare parts can also be ordered separately.

* 1000 is an estimated value. The effective life of the kit depends on the quantity and the kind of sample.



NDA 701 DUMAS NITROGEN ANALYZER

| | |
|--|--|
| Method of analysis: | Dumas method / Combustion |
| Detector: | Innovative autocalibrating TCD (no need for a reference gas) |
| Sample weight: | Up to 1 g |
| Autosampler capacity: | Up to 4 discs, 30 positions each |
| Reproducibility (RSD): | < 0.5% for EDTA standards approx. 100 mg (9.57% N) |
| Recovery : | > 99.5% |
| Detection range: | 0.1 - 200 mg N |
| Detection limit: | 0.003 mg N absolute |
| Combustion temperature: | 1030 °C / 1886 °F |
| Helium (He): | purity 99.999% (grade 5.0) |
| Oxygen (O ₂): | purity 99.999% (grade 5.0) |
| Compressed air or Nitrogen (N ₂): | purity 99.6 % (oil and water free) |
| Helium (He) pressure: | 2 bar |
| Oxygen (O ₂) pressure: | 2.5 bar |
| Compressed air or Nitrogen (N ₂) pressure: | 3 bar |
| Interfaces: | USB, RS232 |
| Power: | 1400 W |
| Power supply: | 230 V / 50 - 60 Hz |
| Weight: | 54 kg / 119 lb |
| Dimensions (WxHxD): | 655 x 510 x 410 mm (655 x 690 x 410 mm including autosampler) 25.8 x 20.1 x 16.1 in (25.8 x 27.0 x 16.0 in including autosampler) |

Constant Commitment to Knowledge Development

Your authorized agent:



www.ert.pt
info@ert.pt

Telf. 217 142 066 - Fax. 217 145 674

Rua Soeiro Pereira Gomes, Lote 5, Cave Drt.
2845-387 Amora Portugal

We reserve the right to make technical alterations
We do not assume liability for errors in printing, typing or transmission

Rev.0 09 2011



VELP Scientifica srl
Via Stazione 16
20865 Usmate (MB) Italy
Tel +39 039 628811
Fax +39 039 6288120
inse@velp.it
www.velp.com